









# HIKVISION

## ZA CENO IN DOBAVLJIVOST POŠLJI POVPRASEVANJE

Tip	Model	Slika	Zahteve	Skupne lasnosti	Opis	Nosilci/doze
Thermal camera	DS-2TD2617B-6/PA(B)		Installation height : 1.5m Face distance : 1.5-2.5m		Thermal : 160 × 120 ; Lens: 6mm ; FOV : 25°×18.7°; Optical : 2688 × 1520 ; Lens: 8mm ; Video mode : Bi-spectrum image fusion ; Accuracy : ±0.5°C Range : 30-45°C	
Thermal camera	DS-2TD2617B-3/PA(B)		Installation height : 1.5m Face distance : 0.8-1.5m		Thermal : 160 × 120 ; Lens: 3mm ; FOV : 50°×37.2°; Optical : 2688 × 1520 ; Lens: 4mm ; Video mode : Bi-spectrum image fusion ; Accuracy : ±0.5°C Range : 30-45°C	Integrated wire hiding box : DS-1260ZJ ; 302700239 Wall corner bracket: DS-1276ZJ-SUS ; 302701678
Thermal camera	DS-2TD2636B-15/P		Installation height : 1.7m-2.5m Face distance : 4.5-9m	1.Support AI face detection, multiple targets detect body temperature at the same time 2. Strobe light and audio alarm, built-in speaker, alarm voice rise when the body temperature is too high, 'body temperature abnormal, please recheck body temperature' 3. Various solutions are available: Accuracy of blackbody scheme is ± 0.3°C; Accuracy of non-blackbody scheme is ± 0.5°C, 4. Quick control, support tripod with easy installation	Thermal : 384 × 288 ; Lens: 15mm ; FOV : 24.2°×18.4°; Optical : 2688 × 1520 ; Lens: 6mm ; Video mode : Bi-spectrum image fusion ; Accuracy : ±0.5°C Range : 30-45°C Working temperature : 10-35°C	Pole mounted : DS-2904ZJ ; DS-2907ZJ ; 302702952
Thermal camera	DS-2TD2637B-10/P		Installation height : 1.7m-2.5m Face distance : 2-7m		Thermal : 384 × 288 ; Lens: 9.7mm ; FOV : 37.5°×28.5°; Optical : 2688 × 1520 ; Lens: 4mm ; Video mode : Bi-spectrum image fusion ; Accuracy : ±0.5°C Range : 30-45°C Working temperature : 10-35°C	
Thermal camera	DS-2TD1217B-6/PA(B)		Installation height : 1.5m Face distance : 1.5-2.5m		Thermal : 160 × 120 ; Lens: 6mm ; FOV : 25°×18.7°; Optical : 2688 × 1520 ; Lens: 8mm ; Video mode : Bi-spectrum image fusion ; Accuracy : ±0.5°C Range : 30-45°C	Wall mount bracket : DS-1273ZJ-140 ; 302700333 Wall corner bracket : DS-1276ZJ-SUS ; 302701678 Junction box : DS-1280ZJ-DM21 ; 302700398
Thermal camera	DS-2TD1217B-3/PA(B)		Installation height : 1.5m Face distance : 0.8-1.5m		Thermal : 160 × 120 ; Lens: 3mm ; FOV : 50°×37.2°; Optical : 2688 × 1520 ; Lens: 4mm ; Video mode : Bi-spectrum image fusion ; Accuracy : ±0.5°C Range : 30-45°C	Tripod : DS-2907ZJ ; 302702952 Wall mount with junction box: DS-1273ZJ-140B ; 302700330
Thermal camera	DS-2TP21B-6AVF/W		Installation height : 1.5m Face distance : 1.0-1.5m		Thermal : 160 × 120, 6.2mm, 25° × 19° Visible : 2MP Bi-spectrum image fusion ; WIFI, Audio alarm Accuracy : ±0.5°C Range : 30-45°C Working temperature : 10-35°C IP54	
Blackbody calibrator	DS-2TE127-G4A		Installation height : 1.7m		Temperature range: 5-50°C Temperature resolution: 0.1°C Accuracy: ±0.1°C Temperature stability: ±0.1°C/h Effective emissivity: 0.97±0.02 Operating temperature: 0-40°C Power : AC 110V-220V	

Ulica Mirka Vadnova 19  
4000 Kranj  
ID številka: SI98795333

 Mars Commerce

tel: 04 280 74 00  
fax: 04 234 08 81  
info@mars-commerce.si